

AE74

Suitable for agricultural application



Excellent Grip Performance

- Big contact area and special tread pattern design provide excellent grip performance.

Lower Soil Compaction

- Low ground pressure design reduces the damage to agricultural land.

Technical Parameter

SIZE	STAR RATING	TRA CODE	AELUS CODE	TYPE	RIM	O.D. (mm)	O.W. (mm)	LI/SS	OTD (mm)
500/45R22.5 IMP	—	—	AE74	TL	AG16.00	1025	505	148D	21
500/60R22.5 IMP	—	—	AE74	TL	AG16.00	1172	512	163D	21
560/45R22.5 IMP	—	—	AE74	TL	AG16.00	1076	549	152D	21
560/60R22.5 IMP	—	—	AE74	TL	AG16.00	1249	560	165D	18
560/60R22.5 IMP	—	—	AE74	TL	AG16.00	1249	560	170D	18
580/65R22.5 IMP	—	—	AE74	TL	AG16.00	1320	576	166D	21
600/50R22.5 IMP	—	—	AE74	TL	AG20.00	1177	621	159D	18
600/50R22.5 IMP	—	—	AE74	TL	AG20.00	1177	621	163D	18
650/50R22.5 IMP	—	—	AE74	TL	AG20.00	1231	652	163D	21
600/55R26.5 IMP	—	—	AE74	TL	AG20.00	1335	624	165D	19
600/55R26.5 IMP	—	—	AE74	TL	AG20.00	1335	624	177D	19
650/55R26.5 IMP	—	—	AE74	TL	AG20.00	1389	645	169D	19
650/55R26.5 IMP	—	—	AE74	TL	AG20.00	1389	645	178D	19
710/50R26.5 IMP	—	—	AE74	TL	AG24.00	1392	727	170D	19
710/50R26.5 IMP	—	—	AE74	TL	AG24.00	1392	727	180D	19
600/60R30.5 IMP	—	—	AE74	TL	AG20.00	1496	604	173D	25
710/50R30.5 IMP	—	—	AE74	TL	AG24.00	1485	729	173D	26
750/60R30.5 IMP	—	—	AE74	TL	AG24.00	1670	763	190D	23
850/50R30.5 IMP	—	—	AE74	TL	AG28.00	1626	853	182D	26