

AS50

Suitable for rocky conditions in pit lane, tunnel and mines



Excellent Cut Resistance

- Smooth pattern and special compound design provide excellent wear and cut resistance.

Outstanding Puncture Resistance

- Wide and thick tread design provides outstanding rock puncture resistance.

Technical Parameter

SIZE	STAR RATING	TRA CODE	AELUS CODE	TYPE	RIM	O.D. (mm)	O.W. (mm)	LI/SS	OTD (mm)
9.00R20 NHS	★★	L-5S	AS50	TT	7.00T	1056	259	154A2	51
12.00R20 NHS	★★	L-5S	AS50	TT	8.50V	1174	312	166A2	57
12.00R24 NHS	★★	L-5S	AS50	TT	8.5	1275	315	175A2	57
17.5R25	★★	L-5S	AS50	TL	14.00/1.5	1415	445	182A2	62
18.00R25	★★	L-5S	AS50	TL	13.00/2.5	1706	502	204A2	77
18.00R25	★★★	L-5S	AS50	TL	13.00/2.5	1706	502	206A2	77
20.5R25	★★★★	L-5S	AS50	TL	17.00/2.0	1538	530	198A2	72
23.5R25	★★	L-5S	AS50	TL	19.50/2.5	1704	600	201A2	77
26.5R25	★★	L-5S	AS50	TL	22.00/3.0	1805	676	209A2	92
26.5R25	★★★★	L-5S	AS50	TL	22.00/3.0	1805	676	217A2	92
29.5R25	★★	L-5S	AS50	TL	25.00/3.5	1905	750	216A2	97
29.5R29	★★	L-5S	AS50	TL	25.00/3.5	2016	768	218A2	100
29.5R29	★★★★	L-5S	AS50	TL	25.00/3.5	2016	768	223A2	100
35/65R33	★★	L-5S	AS50	TL	28.00/3.5	2060	895	224A2	98
35/65R33	★★★★	L-5S	AS50	TL	28.00/3.5	2060	895	229A2	98